

基本订货单位

■订货注意事项

订货时，请以最小包装单位的整数倍指定订货数量。

品种·系列名称	额定静电容量 (μF)		散装	编带型产品
				折叠包装式
QXK-(ZH)	250VDC	0.047 ~ 0.1	※	1,000
		0.15 ~ 1.0		500
		1.5 ~ 3.3		—
	400VDC	0.022 ~ 0.047	※	1,000
		0.068 ~ 0.22		500
		0.33		400
		0.47		300
	630VDC	0.68 ~ 1.5	※	—
		0.01 ~ 0.015		1,000
0.022 ~ 0.068		500		
QXK	250VDC	0.1	※	400
		0.15 ~ 0.47		—
		0.01 ~ 0.33		1,000
		0.47 ~ 1.0		500
	400VDC	1.5	※	400
		2.2 ~ 10.0		—
		0.01 ~ 0.1		1,000
		0.15 ~ 0.22		500
	630VDC	0.33 ~ 0.47	※	400
		0.68 ~ 2.2		—
		0.01 ~ 0.047		1,000
		0.068 ~ 0.15		500
QXP	250VDC	0.22	※	300
		0.33 ~ 2.2		—
		0.047 ~ 0.068		1,000
		0.1 ~ 0.15		500
		0.22 ~ 0.33		400
	400VDC	0.47 ~ 0.68	※	300
		1.0 ~ 3.3		—
		0.022 ~ 0.033		1,000
		0.047 ~ 0.068		500
	630VDC	0.1 ~ 0.15	※	400
		0.22 ~ 0.33		300
		0.47 ~ 1.5		—
		0.01 ~ 0.015		1,000
	800VDC	0.022 ~ 0.068	※	500
		0.1		400
		0.15		300
0.22 ~ 0.68		—		
0.01		1,000		
QXT	400, 630VDC	0.0068 ~ 0.1	※	—
QXL	125, 250VAC	0.01 ~ 1.0	※	※
QAK, QAP	250, 400, 630VDC	0.1 ~ 10.0	※	—
QYX	50VDC	0.001 ~ 0.022	1,000	2,000
		0.033 ~ 0.22		1,000
		0.33 ~ 0.47		—
	100VDC	0.001 ~ 0.022	1,000	2,000
		0.033 ~ 0.1		1,000
		0.15 ~ 0.47		—
EEC		所有额定值	100	—
EXH		所有额定值	100	—

※请参照薄膜电容器手册 自动插入用编带品详情页。